

Maintenance carried out by Operator								
TASK		WHEN	FOLLOW UP (DATE/NAME)					
1.	Check the level in the cooling unit, fill up with the cooling fluid if necessary.	Daily						
2.	Check all connections (hoses, power cable, exhausts).	Daily						
3.	Clean the lamps, the vacuum table, the light finisher drawer with alcohol or glass cleaner and clean cotton wipers.	Monthly						
4.	Check the vacuum foil, replace if necessary.	Monthly						
5.	Clean the equipment from dust and dirt and vacuum clean the exposure fans openings.	Monthly						
6.	Carry out the exposure lamps UV output measurement.	Monthly						
7.	Check the proper function of the emergency switch.	Every 3 months						
8.	Replace the exposure lamps.	Replace if output is below 14 mW/cm <sup>2</sup> or exceeding 750 working hours						
9.	Replace the light finisher UVA lamps.	Replace if output is below 14 mW/cm <sup>2</sup> or exceeding 750 working hours						
10.	Replace the light finisher UVC lamps.	Replace if exceeding 1000 working hours						

Maintenance carried out by Service Technician								
TASK		WHEN	FOLLOW UP (DATE/NAME)					
1.	Check the pump and cooling unit operation.	Every 3 months						
2.	Check the proper function of safety interlock switches (lid and light finisher drawer and panel).	Every 3 months						
3.	Check the gas springs of the lid.	Every 3 months						
4.	Measure the accuracy of the temperature sensors of the lamps and exposure table.	Every 3 months						
5.	Check the outer lamps indicators.	Every 3 months						
6.	Safety check of electrical and mechanical components. Adjust if necessary.	Every 3 months						
7.	Check the proper function of the air pressure switch of the dryer exhaust.	Every 3 months						
8.	Check the proper function of the water level and flow sensors.	Every 3 months						
9.	Replace the cooling fluid and flush the system.	Every 3 months						