Maintenance Chart Plate Processor 85 Wash **▼** OPERATION **SECTION** ➤ Pre-heat Pre-wash Developer Gum Dryer Cleaning Time 1. Check the replenisher container. Daily Daily ~ 2 min. 2. Check the waste container. Daily ~ 2 min. 3. Safety check of the mechanical components. Daily ~ 5 min. Daily 4. Clean the transport rollers from residues. ~ 5 min. 5. Check the developer level. Daily ~ 5 min. Daily 2) Daily 2) 6. Change the water and clean the section. ~ 10 min. 1) 7. Change the chemistry/filter (optional). ~ 30 min. 8. Main cleaning: Pre-wash 3) By chemistry a. Clean the brush roller. change or ~ 1 hour b. Clean the tank with the "PROCESSOR CLEANER". once a month c. Clean the tubes and drain with backflush. 9. Main cleaning: Dev 3) a. Clean all rollers and guides. By chemistry b. Clean the tanks with the "PROCESSOR CLEANER". change or ~ 1 hour c. Clean the spray tubes with brush. once a month d. Clean the tubes and drain with backflush. 10. Main cleaning: Wash 3) By chemistry a. Clean the brush roller. change or ~ 1 hour b. Clean the tank with the "PROCESSOR CLEANER". once a month c. Clean the tubes and drain with backflush. 11. Main cleaning: Gum 4) By chemistry a. Flush the gum pumps and solenoid. 4) change or ~ 1 hour b. Clean the rollers. once a month c. Clean the tank with the "PROCESSOR CLEANER". 4) 12. Cleanining of circulation pumps. 5) **Every 3 months** ~ 5 min. 13. Cleanining of replenish pumps. 5) **Every 3 months** ~ 15 min. **Every 3 months** 14. Install Preventive Maintenance Kit Minor (bearings - 0-rings - V-seals). 6) Every year or 500 hours ~ 1 - 2 hours 15. Install Preventive Maintenance Kit Medium (gears - bearings - V-seals - poppet valves - guides -Every 2 years or 1,000 hours ~ 3 - 4 hours bushings - pump head). 7) 16. Install Preventive Maintenance Kit Major (gears - bearings - guides), 8) Every 4 years or 2,000 hours ~ 5 - 6 hours 1) Change of chemistry/filter is based on the type of chemistry (filter is not standard). Chemistry type: 2) Machine with water circulation system built in. 3) See the cleaning instructions in the User's Manual. Chemistry change: 4) Use lukewarm water. Filter change: 5) See the instructions in the processor Service Manual.